

Product Information

Longlife P5 SAE 5W-40

is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

Extended oil change intervals as per manufacturer's instructions.

Longlife P5 SAE 5W-40 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

Longlife P5 SAE 5W-40 offers maximum operational safety in all driving conditions, for example in extreme stop-and-go traffic in big cities, as well as during high-speed motorway driving.

Longlife P5 SAE 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines.

In compliance to EEC regulation the quality of this product is equivalent according to the following standards/specifications:

- API: SN
- ACEA: A3 / B4

Approval: MB 229.5

Practice-proven and tested in aggregates with filling rules/ACC. To:

- ♦ BMW Longlife-01
- ♦ VW-Norm 502 00 und 505 00
- ♦ Porsche A40
- ♦ Opel GM-LL-B-025
- ♦ Renault RN 0700 und RN 0710
- ♦ MB 229.3

Longlife P5 SAE 5W-40 shows in the practical use of the following benefits:

- Excellent cold starting properties, even at low temperatures below -30°C.
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources

Technical specifications:

| Properties | Density at 15°C | Viscosity at 100°C | Colour | Pourpoint | Viscosity-Index |
|---------------|-------------------|--------------------|---------|--------------|-----------------|
| Testing under | DIN ISO 12 185 | DIN 51 562 | visuell | DIN ISO 3016 | DIN ISO 2909 |
| Unit | kg/m ³ | mm ² /s | - | °C | VI |
| Wert | 846 | 13,8 | yello | -42 | 170 |

All declared values are approximate and subject to standard production variations.

2085*11052016

To the best of our knowledge all information reflects the current state of findings and our development. Subject to Change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.